

Declaration of Performance

ICID [304 Liner] – System Chimney

GB-016-DOP-13-11-15

Declaration of Performance

No. GB-016-DOP-13-11-15

1. Unique identification code of the product-type:

**Multi-wall Metal System Chimney (with 304 Liner)
EN 1856-1**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

Manufacturer Identification(s):

ICID, Eco ICID, HLX 2000, Anderson Flue

| | | | | | | | |
|---------------|----------------|-------------|-----------|----------|-----------|---------------|------------|
| Designation 1 | DN (125 – 300) | T450 | N1 | D | Vm | L20050 | G60 |
| Designation 2 | DN (125 – 300) | T450 | N1 | D | Vm | L20050 | G50 |

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Convey the products of combustion from heating appliances to the outside atmosphere

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):

**Schiedel Chimney Systems Ltd
Crowther Estate
Washington**

Tyne & Wear

**NE38 0AQ
UK
Telephone: +44 (0) 191 4161150
Fax: +44 (0) 191 4151263
Email: sales@schiedel.co.uk**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

n/a

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 2+ and System 4

7. Notified factory production control certification body No. **0036** performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificate of conformity of the factory production control.

TÜV Industrie Service GmbH TÜV Süd Gruppe
Ridlerstraße 65
D-80339 München

8. Declared performance

| Essential characteristics and clauses to EN 1856-1 | Performance | Harmonized technical specification |
|--|---|------------------------------------|
| Compressive strength | Designation(s) 1 & 2: npd | EN 1856-1: 2009 |
| Chimney sections, fittings and supports | For further information see installation instructions | |
| Resistance to fire | Designation 1: DN (125 – 300) : T450 G60 *Tested fully enclosed in a combustible shaft; floor penetration fully ventilated with ventilated fire-stop plates. Designation 2: DN (125 – 300) : T450 G50 *Tested fully enclosed in a non-combustible shaft; floor penetration fully insulated with solid fire-stop plates.. | |
| Gas tightness /leakage | Designation(s) 1 & 2: DN (125 – 300) : N1 (Passed) | |
| Flow resistance of chimney sections | Designation(s) 1 & 2: DN (125 – 300) : 1mm | |
| Flow resistance of chimney fittings | Zeta 0.3 according EN 13384-1 | |
| Flow resistance of terminals | Zeta 0.5 according EN 13384-1 | |
| Thermal resistance | Designation(s) 1 & 2: DN (125 – 300) : 0.37 m ² K/W tested at 200°C | |
| Thermal shock resistance | Designation(s) 1 & 2: | |
| Sootfire Resistance: | DN (125 – 300) : Yes. | |
| Thermal performance under normal operating conditions: | Designation(s) 1 & 2: DN (125 – 300) : T450 | |

| Essential characteristics and clauses to EN 1856-1 | Performance | Harmonized technical specification |
|--|--|------------------------------------|
| Flexural tensile strength (only for means of connection for chimney sections and fittings) | Designation(s) 1 & 2: npd | EN 1856-1: 2009 |
| Non vertical installation | Designation(s) 1 & 2: DN (125 – 300) between supports $\leq 3\text{m}$ at 90° | |
| Components subject to wind load | Designation(s) 1 & 2: <u>DN (125 – 300)</u> $\leq 2\text{ m}$ above last support $\leq 4\text{ m}$ between supports | |
| Durability Water and vapour diffusion resistance | Designation(s) 1 & 2: DN (125 – 300) : Yes | |
| Condensate penetration resistance | Designation(s) 1 & 2: DN (125 – 300) : No designated Dry | |
| Against corrosion | Designation(s) 1 & 2: DN (125 – 300) : Vm | |
| Freeze thaw resistance | Designation(s) 1 & 2: DN (125 – 300) : Yes | |


9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Michael Ball: Chief Executive Officer
.....
(name and function)

Washington, 13th Nov 2015
.....

(place and date of issue)


.....
(signature)